


# APLÔ

3410 - LAMP H.10 IN.  
DESIGN BY TRISTAN LOHNER

RESIDENTIAL CONTRACT INTENSIVE



Polyethylene diffuser

Aluminum frame

ABS base

Technology : integrated LED - Luminous flux : 70 lm

Switch type : push button

Function of the switch : change the light temperature (long click, 3 s),  
change the brightness (short click, 1 s)

Lighting mood :

Position 1 cool white (6000°K) 100% brightness

Position 2 cool white (6000°K) 50% brightness

Position 3 warm white (3000°K) 100% brightness

Position 4 warm white (3000°K) 50% brightness

Type of power supply : battery - Battery life : Min. (100%) 7 h - Max. 15 h

Battery use cycles : 300 cycles

Recharge time : 3h - Type of recharge : USB, cable (supplied) 39 in.

Bypass to prevent battery damage during wired use

0.5 A - 5 V - 0.5 W - IP54 (ingress protection) | IK 10 (impact resistance) | CE | FCC | UKCA

Energy rating : F


Powered by Smart & Green

Compatible with :

WALL LIGHT BRACKET - APLÔ

SUSPENSION STRAP - APLÔ

MAGNETIC BASE - APLÔ



0.82 lb

- |        |                 |        |                |
|--------|-----------------|--------|----------------|
| 341014 | ● Nutmeg        | 341073 | ● Honey        |
| 341020 | ● Red Ochre     | 341082 | ● Cactus       |
| 341021 | ● Acapulco Blue | 3410B9 | ● Black Cherry |
| 341047 | ● Anthracite    | 3410A5 | ● Clay Grey    |

NEW  
NEW



APLÔ & BISTRO